



US006636344B2

(12) **United States Patent**  
**Akasaka et al.**

(10) **Patent No.:** **US 6,636,344 B2**  
(45) **Date of Patent:** **Oct. 21, 2003**

(54) **RAMAN AMPLIFIER, OPTICAL REPEATER,  
AND RAMAN AMPLIFICATION METHOD**

(75) Inventors: **Yuuichi Akasaka**, Chiyoda-ku (JP);  
**Yoshihiro Emori**, Chiyoda-ku (JP);  
**Shu Namiki**, Chiyoda-ku (JP)

(73) Assignee: **The Furukawa Electric Co., Ltd.**,  
Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/944,601**

(22) Filed: **Sep. 4, 2001**

(65) **Prior Publication Data**

US 2002/0021487 A1 Feb. 21, 2002

**Related U.S. Application Data**

(63) Continuation of application No. 09/527,748, filed on Mar.  
17, 2000, now Pat. No. 6,292,288, which is a continuation-  
in-part of application No. PCT/JP99/03944, filed on Jul. 23,  
1999.

(30) **Foreign Application Priority Data**

Jul. 23, 1998	(JP)	10-208450
Jul. 27, 1998	(JP)	10-210822
Feb. 12, 1999	(JP)	11-034769
Feb. 12, 1999	(JP)	11-034833
Jan. 14, 2000	(JP)	2000-006567

(51) **Int. Cl.<sup>7</sup>** ..... **H01S 3/10**

(52) **U.S. Cl.** ..... **359/334; 359/341.31; 372/6;**  
372/7

(58) **Field of Search** ..... 359/334, 341.3,  
359/341.31, 341.33; 372/3, 6, 70

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,616,898 A 10/1986 Hicks, Jr.

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

EP 0 615 356 A1 \* 9/1994 ..... 359/156

(List continued on next page.)

**OTHER PUBLICATIONS**

Masuda et al, ECOC '97, Sep. 25, 1997, Conf. Pub. No. 448,  
pp 73-76.\*

(List continued on next page.)

*Primary Examiner*—Nelson Moskowitz

(74) *Attorney, Agent, or Firm*—Oblon, Spivak, McClelland,  
Maier & Neustadt, P.C.

(57) **ABSTRACT**

A Raman amplifier according to the present invention comprises a plurality of pumping means using semiconductor lasers of Fabry-Perot, DFB, or DBR type or MOPAs, and pumping lights outputted from the pumping means have different central wavelengths, and interval between the adjacent central wavelength is greater than 6 nm and smaller than 35 nm. An optical repeater according to the present invention comprises the above-mentioned Raman amplifier and adapted to compensate loss in an optical fiber transmission line by the Raman amplifier. In a Raman amplification method according to the present invention, the shorter the central wavelength of the pumping light the higher light power of said pumping light. In the Raman amplifier according to the present invention, when a certain pumping wavelength is defined as a first channel, and second to n-th channels are defined to be arranged with an interval of about 1 THz toward a longer wavelength side, the pumping lights having wavelengths corresponding to the first to n-th channels are multiplexed, and a pumping light having a wavelength spaced apart from the n-th channel by 2 THz or more toward the longer wavelength side is combined with the multiplexed light, thereby forming the pumping light source. The pumping lights having wavelengths corresponding to the channels other than (n-1)-th and (n-2)-th channels may be multiplexed, thereby forming the pumping light source. The pumping lights having wavelengths corresponding to the channels other than (n-2)-th and (n-3)-th channels may be multiplexed, thereby forming the pumping light source.

**41 Claims, 66 Drawing Sheets**

